

PDU & Maintenance Bypass Switch Selection Guide

MODEL		HotSwap MBS-Rack
Current Rating		16 A max. for 208/220/230/240 VAC / 20 A max. for 110/115/120/127 VAC
Voltage Rating		208/220/230/240 VAC or 110/115/120/127 VAC
Master/Slave Function		Yes. When power consumption in Master outlet is lower than 20W ($\pm 5W$), it will shut off the power for slave outlets.
CONNECTION		
Input	AC Power	1 x IEC (16 A) connector and 1 x customized plug cable
	UPS Input	1 x IEC (16 A) connector and 1 x cable (16A - 10A IEC cable for 1K/2K, 16A - 16A IEC cable for 3K)
	UPS Output	1 x IEC (16 A) connector and 1 x cable (16A - 10A IEC cable for 1K/2K, 16A - 16A IEC cable for 3K)
Output	IEC	5 x IEC 10A sockets + 1 x IEC 16A socket (with 2 circuit breakers)
	Schuko (NL/LU)	4 x Schuko 16A sockets
	USE (BE/FR)	4 x USE 16A sockets
	HW	HW P+N
PHYSICAL		
Dimension, D x W x H(mm)	IEC	80 x 438 x 50
	Schuko	80 x 438 x 60
	UK	
	NEMA	80 x 438 x 50
Net Weight (kgs)		1.5
ENVIRONMENT		
Operating Temperature		20-90 % RH @ 0- 45°C (non-condensing)
NEXT PARTNUMBERS		
HotSwap Bypass IEC		88002
HotSwap Bypass BE/FR		88004
HotSwap Bypass NL/LU		88003
HotSwap Bypass HW (6/10 kVA)		88005

Product specifications are subject to change without further notice