



Mint +

- 700VA/1000VA/1200VA/1500VA line interactive UPS
- Built-in super smart charger, shorten 50% of charging time
- Excellent microprocessor control guarantees high reliability
- Boost and buck AVR for voltage stabilization
- Auto restart while AC is recovering
- Simulated sine wave output
- Off-mode charging
- Cold start function
- USB communications port and RJ-11/RJ-45 protection
- 5V USB charger port for mobile devices
- LCD panels for selections & real-time UPS status
- Easy replaceable & hot-swappable battery
- NEXTVision shutdown software suite
- 3 years NEXT Onsite warranty



Mint + Selection Guide

MODEL	Mint+ 700	Mint+ 1000	Mint+ 1200	Mint+ 1500
CAPACITY	700 VA / 420 W	1000 VA / 600 W	1200 VA / 720 W	1500 VA / 900 W
INPUT				
Voltage	220/230/240 VAC			
Voltage Range	170-280 VAC			
Frequency Range	50 Hz - 60 Hz (auto-sensing)			
OUTPUT				
Output Voltage	220/230/240 VAC			
AC Voltage Regulation (Batt. Mode)	±10%			
Frequency Range (Batt. Mode)	50 Hz or 60 Hz ±1 Hz			
Transfer Time	Typical 2-6 ms, 10ms max.			
Waveform (Batt. Mode)	Simulated Sinewave			
BATTERY				
Battery Type & Number	12 V / 9 Ah x 1	12 V / 9 Ah x 1	12 V / 9 Ah x 2	12 V / 9 Ah x 2
Typical Recharge Time	4-6 hours to recover 90% capacity			
PROTECTION				
Full Protection	Overload, discharge, and overcharge protection			
INDICATORS				
LCD Display	AC Mode, Battery Mode, Load Level, Battery Level, Input Voltage, Output Voltage, Overload, Fault, and Low Battery			
ALARM				
Battery Mode	Sounding every 10 seconds			
Low Battery	Sounding every second			
Overload	Sounding every 0.5 second			
Battery Replacement Alarm	Sounding every 2 seconds			
Fault	Continuously sounding			
PHYSICAL				
Dimension, D x W x H (mm)	288 x 99 x 280	288 x 99 x 280	410 x 99 x 280	
Net Weight (kgs)	7.9	8.5	11.8	13.1
ENVIRONMENT				
Humidity	0-90% RH @ 0-40°C. (non-condensing)			
Noise Level	Less than 40dB			
MANAGEMENT				
USB Port	Supports Windows®, Linux, Unix, and MAC			
NEXT PART NUMBERS				
MINT+ BE/FR	44244	44245	44246	44247
MINT+ NL/LU	44248	44249	44250	44251
MINT+ IEC	-	44253	-	44254
NEXT 5+ warranty extension	11002	11002	11003	11003

Product specifications are subject to change without prior notice