



OFFICE PROTECTION STATION

- 600VA/800VA standby UPS
- High frequency design
- Compact size with stand and mounting flexibility
- Suitable for active PFC equipped personal computers
- Auto restart while AC is recovering
- Simulated sine wave output
- Cold start function
- 3 years NEXT Onsite warranty



Office Protection Station Off-Line UPS Selection Guide

MODEL	Office Protection Station 600	Office Protection Station 800
CAPACITY	600 VA / 300 W	800 VA / 420 W
INPUT		
Voltage	220/230/240 VAC	
Acceptable Voltage Range	170 - 270 VAC	
Frequency	55Hz or 65Hz (Auto sensing)	
OUTPUT		
Output Power Factor	0,5	0,525
Nominal Output Voltage	230V _{AC}	
Voltage Regulation (Battery Mode)	±10%	
Frequency Range (Battery Mode)	50Hz/60Hz ±1Hz	
Waveform (Batt. Mode)	Modified Sinewave	
EFFICIENCY		
Line Mode	>95%	
Battery Mode	>70%	
BATTERY		
Battery Type & Number	12 V / 5 Ah x 1	12 V / 9 Ah x 1
Typical Recharge Time	8 hours recover to 90% capacity	
INDICATORS		
AC Mode	Green lighting	
Battery Mode	Green flashing every 10 seconds	
Low Battery (Batt. Mode)	Green flashing every second and red lighting	
Fault	Red lighting	
ALARM		
Battery Mode	Sounding every 10 seconds	
Low Battery (Batt. Mode)	Sounding every second	
Fault	Continuously sounding	
PHYSICAL		
Dimension, W x H x D (mm)	320 x 125 x 86	335 x 170 x 92,5
Net Weight (kgs)	3,7	5
ENVIRONMENT		
Humidity	0-90 %	
Operating Temperature	0- 40°C (non-condensing)	
NEXT PARTNUMBERS		
Office Protection Station BE/FR	22314	22315
Office Protection Station NL/LU	22317	22318
NEXT 5+ warranty extension	11002	11002

Product specifications are subject to change without further notice